

TENNESSEE TRAILERS, INC.
P. O. BOX 398
SODDY-DAISY, TN. 37379

9/19/84

B
7/12/85
Kup
3/8/85

ADMINISTRATOR, NATIONAL HIGHWAY
TRAFFIC SAFETY ADMINISTRATION
400 SEVENTH STREET, S.W.
WASHINGTON, DC, 20590
ATTN: VIN COORDINATOR

ORIGINAL

DEAR SIR:

01-22-N1B-1880

IN COMPLIANCE WITH FEDERAL STANDARD 115 S6.3, THE INFORMATION NECESSARY TO DECIPHER THE CHARACTERS CONTAINED IN OUR TRAILER VIN'S FOLLOWS TO BE EFFECTIVE SEPTEMBER 19, 1984.

THE FIRST SECTION, THE MANUFACTURER IDENTIFIER ASSIGNED TO US BY THE SAE, IS ITP.

THE SECOND SECTION OF 5 CHARACTERS IDENTIFIES THE REQUIRED ATTRIBUTES OF OUR TRAILERS AS FOLLOWS:

1ST AND 2ND CHARACTERS - TYPE AND MODEL OF TRAILER

THE 1ST CHARACTER IDENTIFIES THE TRAILER TYPE, LETTERS A, B, C, D OR E IDENTIFY A BOAT TRAILER. LETTERS F, G, H, J OR K IDENTIFY A CARGO/UTILITY TRAILER. LETTERS L, M OR N IDENTIFY A CAMPER TRAILER. LETTERS P OR R IDENTIFY A MOTORCYCLE TRAILER. LETTERS S OR T IDENTIFY A SNOWMOBILE TRAILER. LETTER U, V IDENTIFY A MOBILE EQUIPMENT TRAILER. LETTERS W, X, Y OR Z IDENTIFY AN OTHER SPECIAL PURPOSE TRAILER.

THE 1ST AND 2ND CHARACTERS TOGETHER IDENTIFY THE SPECIFIC MODEL OF OUR TRAILERS AS FOLLOWS:

MODEL DESIGNATION	CHARACTERS 1 AND 2	MODEL DESIGNATION	CHARACTER 1 AND 2
CC-S-DX	B 5	BB-S-DX	B 7
BB-S-DX	B 7	DC DOLLY	C W
I-S-DX	B 9	NN22	C M
CC-STD	C A	NN24	C N
CC-DX	C B	FF	C P
BB-STD	C C	800	A A
BB-DX	C D	500	B 2
I-DX	C F	950	A B
1000	A C	1150	A E
2900	B X	750	C S
3200	B Z	3900	B 1
NN17	B 3	5000	C V
LBJ-50	C X	1159	C Y
MM	D 2	FF-DX	D 3
2000	D 4		

3RD CHARACTER - GAWR, TIRE AND RIM INFORMATION

THE STANDARD GAWR, TIRE AND RIM INFORMATION OF OUR TRAILERS IS INDICATED AS FOLLOWS:

A - GAWR 1010 WITH 4.80-8 B	TIRES 8X3.75	RIMS AT 60 PSI
B - GAWR 1280 WITH 5.70-8 B	TIRES 8X3.75	RIMS AT 50 PSI
C - GAWR 1430 WITH 5.70-8 B	TIRES 8X3.75	RIMS AT 50 PSI
D - GAWR 1560 WITH 4.80-12 B	TIRES 12X4.00	RIMS AT 60 PSI
E - GAWR 1635 WITH 5.20-12 B	TIRES 12X4.00	RIMS AT 55 PSI
F - GAWR 2095 WITH E78-14 B	TIRES 14X6.00	RIMS AT 32 PSI
G - GAWR 2455 WITH E78-14 B	TIRES 14X6.00	RIMS AT 32 PSI
H - GAWR 3110 WITH F78X14 C	TIRES 14X6.00	RIMS AT 55 PSI
J - GAWR 1275 WITH 4.80-12 B	TIRES 12X3.75	RIMS AT 60 PSI
K - GAWR 1430 WITH A78-13 B	TIRES 13X5.50	RIMS AT 32 PSI
L - GAWR 1650 WITH 5.30-12 B	TIRES 12X4.00	RIMS AT 55 PSI
M - GAWR 1790 WITH A78-13 B	TIRES 13X5.50	RIMS AT 32 PSI
N - GAWR 1810 WITH A78-13 B	TIRES 13X5.50	RIMS AT 32 PSI
U - GAWR 2925 WITH G78-14 B	TIRES 14X6.00	RIMS AT 32 PSI
V - GAWR 3145 WITH F78X14 C	TIRES 14X6.00	RIMS AT 55 PSI
Y - GAWR 1925 WITH A78-13 B	TIRES 13X5.50	RIMS AT 32 PSI
2 - GAWR 2165 WITH E78-14 B	TIRES 14X6.00	RIMS AT 32 PSI
3 - GAWR 2450 WITH F78X14 C	TIRES 14X6.00	RIMS AT 55 PSI
4 - GAWR 3200 WITH F78-14 C	TIRES 14X6.00	RIMS AT 55 PSI

4TH CHARACTER - LENGTH OF TRAILER

TRAILER LENGTHS TO THE NEAREST FOOT ARE CODED AS FOLLOWS:

A - 5 FEET	M - 17 FEET	Z - 28 FEET
B - 7 FEET	N - 18 FEET	
C - 8 FEET	P - 19 FEET	
D - 9 FEET	R - 20 FEET	
E - 10 FEET	S - 21 FEET	
F - 11 FEET	T - 22 FEET	
G - 12 FEET	U - 23 FEET	
H - 13 FEET	V - 24 FEET	
J - 14 FEET	W - 25 FEET	
K - 15 FEET	X - 26 FEET	
L - 16 FEET	Y - 27 FEET	

5TH CHARACTER - AXLE CONFIGURATION

- 1 - SEMI TRAILER - SINGLE AXLE
- 2 - SEMI TRAILER - TANDEM AXLE

- 3 - SEMI TRAILER - TRI-AXLE
- 4 - FULL TRAILER - ONE STEERABLE AND ONE TRAILING AXLE
- 5 - FULL TRAILER - ONE STEERABLE AND TWO TRAILING AXLES

THE THIRD SECTION CONTAINS THE FOLLOWING SPECIAL INFORMATION:

1ST CHARACTER - MODEL YEAR PER TABLE II FEDERAL STANDARD 115

2ND CHARACTER - PLANT IDENTIFICATION

1 - SODDY-DAISY, TN. PLANT

3RD CHARACTER - ALTERNATE GAWR, TIRE AND RIM INFORMATION

THE 3RD CHARACTER INDICATES ALTERNATE GAWR, TIRE AND RIM INFORMATION, IF SUCH IS LISTED ON THE TRAILER CERTIFICATION PLATE, USING THE CHARACTERS ESTABLISHED IN THE 3RD CHARACTER OF THE 2ND SECTION.

A ZERO INDICATES NO ALTERNATE GAWR, TIRE AND RIM INFORMATION.

4TH - 8TH CHARACTERS - SEQUENTIAL NUMBER

SINCERELY YOURS,



SHARON BOOK
TENNESSEE TRAILERS, INC.