B 8/25/85 VSS
Tdg

RM

TRAILEX, INC.
60 INDUSTRIAL PARK DR.
CANFIELD OH 44406

49

6/18/85

ORIGINAL

ADMINISTRATOR, NATIONAL HIGHWAY
TRAFFIC SAFETY ADMINISTRATION
400 SEVENTH STREET, S.W.
WASHINGTON, DC. 20590
ATTN: VIN COORDINATOR

01-22-N11B-1990

DEAR SIR:

IN COMPLIANCE WITH FEDERAL STANDARD 115 S6.3, THE INFORMATION NECESSARY TO DECIPHER THE CHARACTERS CONTAINED IN OUR TRAILER VIN'S FOLLOWS TO BE EFFECTIVE JULY 1, 1985.

THE FIRST SECTION, THE MANUFACTURER IDENTIFIER ASSIGNED TO US BY THE S.A.E. IS 1XT.

THE SECOND SECTION OF FIVE CHARACTERS IDENTIFIES THE REQUIRED ATTRIBUTES OF OUR TRAILERS AS FOLLOWS:

FIRST AND SECOND CHARACTERS - TYPE AND MODEL OF TRAILER

THE FIRST CHARACTER IDENTIFIES THE TRAILER TYPE:

A, B, C, D OR E -- BOAT TRAILER
F, G, H, J OR K -- CARGO/UTILITY TRAILER
L, M OR N -- CAMPER TRAILER
P OR R -- MOTORCYCLE TRAILER
S OR T -- SNOWMOBILE TRAILER
U OR V -- MOBILE EQUIPMENT TRAILER
W, X, Y OR Z -- ANY OTHER SPECIAL PURPOSE TRAILER.

THE FIRST AND SECOND CHARACTERS TOGETHER IDENTIFY THE SPECIFIC MODEL OF OUR TRAILERS AS FOLLOWS:

MODEL DESIGNATION	CHARACTERS 1 AND 2		MODEL DESIGNATION	CHARACTERS 1 AND 2	
200	A	A	400	A	B
400	A	C	405W.T.	A	D
405W.T.	A	E	405A-16	A	F
400FSC	A	G	500	A	H
500	A	J	505	A	K
505	A	L	700	A	M
70DD/CB	A	N	700SCC	A	P
700ECC	A	R	850	A	S
900	A	T	1100	A	U
1400	A	V	1700	A	W
1700TD	A	X	1700TD	A	Y

MODEL DESIGNATION	CHARACTERS 1 AND 2		MODEL DESIGNATION	CHARACTERS 1 AND 2	
2000SA	A	Z	400HC-14	B	A
400HC-16	B	B	400HC-14	B	C
400HC-16	B	D	400HC-18	B	F
400HC-18	B	G	400SC-20	B	H
2400STIL	B	J	6000-2A	C	A
4100A	C	B	3000SA-A	C	C
3000A	C	D	2400A	C	E
2400A	C	F	2000A	C	G
2000A	C	H	1700A	C	J
1100A	C	K	2000	D	A
2000	D	B	2000PY23	D	C
2400	D	E	2400	D	F
3000SA	D	G	3000	D	H
4100-2X	D	J	4100-3X	D	K
6000-2X	D	L	8500-3X	D	M
2100	E	A	2400T	E	B
2600T	E	C	2700	E	D
2900	E	E	3300T	E	F
1200	E	G	9000	E	H
400 HC-UL	E	J	400 UL	E	K
6522 TS	F	A	7022-TS	F	B
7522-TS	F	C	1682 TB	G	B
850 C	P	A	800X34	S	A
800X44	S	B	800X72	S	C
800X86	S	D	800X86	S	E
1600X86	S	F	800X51	S	G
800X60	S	H	800X70	S	J
800X34	T	A	800X44	T	B
800X72	T	C	800X51	T	G
800X60	T	H	60SA	W	A
60	W	B	66	W	C
60HD	W	D	66HD	W	F
66HD/SA	W	G	70SS/SA	W	H
70SS	W	J	6631HS	W	K
7031HS	W	L	7041HS	W	M
7041HSLB	W	N	756HSLB	W	P
756HS	W	R	60SA	X	A
60	X	B	66	X	C
60HD	X	D	66HD	X	E
66HD	X	F	66HD/SA	X	G
70SS/SA	X	H	70SS	X	J
6631HS	X	K	7031HS	X	L
7041HS	X	M	7041HSLB	X	N
756HSLB	X	P	756HS	X	R
7541-HS	X	S	1000-6	X	T
1000-8	X	U			

THIRD CHARACTER - GAWR, TIRE AND RIM INFORMATION

THE STANDARD GAWR, TIRE AND RIM INFORMATION OF OUR TRAILERS IS INDICATED AS FOLLOWS:

A - GAWR	500	WITH 4.80-8 A	TIRES 8X3.75	RIMS,	AT	30 PSI
B - GAWR	780	WITH 4.80-8 A	TIRES 8X3.75	RIMS,	AT	30 PSI
C - GAWR	500	WITH 4.80-8 B	TIRES 8X3.75	RIMS,	AT	60 PSI
D - GAWR	1180	WITH 4.80-8 B	TIRES 8X3.75	RIMS,	AT	60 PSI
E - GAWR	1430	WITH 5.70-8 B	TIRES 8X4.50	RIMS,	AT	50 PSI
F - GAWR	1820	WITH 5.70-8 C	TIRES 8X4.50	RIMS,	AT	75 PSI
G - GAWR	1200	WITH 4.80-12 B	TIRES 12X3.75	RIMS,	AT	60 PSI
H - GAWR	1560	WITH 4.80-12 B	TIRES 12X3.75	RIMS,	AT	60 PSI
J - GAWR	1680	WITH 5.30-12 B	TIRES 12X4.25	RIMS,	AT	55 PSI
K - GAWR	2000	WITH 6.50-13 STB	TIRES 13X4.50	RIMS,	AT	35 PSI
L - GAWR	2120	WITH 6.50-13 STB	TIRES 13X4.50	RIMS,	AT	35 PSI
M - GAWR	2120	WITH 6.50-13 STC	TIRES 13X4.50	RIMS,	AT	50 PSI
N - GAWR	2630	WITH 6.50-13 STC	TIRES 13X4.50	RIMS,	AT	50 PSI
P - GAWR	3500	WITH 8.55-15 STC	TIRES 15X5.50	RIMS,	AT	50 PSI
R - GAWR	1240	WITH 16.5X6.5-8 B	TIRES 8X5.375	RIMS,	AT	45 PSI
S - GAWR	2000	WITH 20.5X8.0-10 C	TIRES 10X6.00	RIMS,	AT	50 PSI
T - GAWR	2000	WITH 20.5X8.0-10 C	TIRES 10X6.00	RIMS,	AT	50 PSI
U - GAWR	2500	WITH 20.5X8.0-10 D	TIRES 10X6.00	RIMS,	AT	70 PSI
V - GAWR	5580	WITH 8-14.5 LTF	TIRES 14.5X6.00	RIMS,	AT	100 PSI
W - GAWR	2200	WITH B78-13 STC	TIRES 13X4.50	RIMS,	AT	50 PSI

FOURTH CHARACTER - LENGTH OF TRAILER

TRAILER LENGTHS TO THE NEAREST FOOT ARE CODED AS FOLLOWS:

A) - 6 FEET	M) - 17 FEET	Z) - 28 FEET
B) - 7 FEET	N) - 18 FEET	1) -
C) - 8 FEET	P) - 19 FEET	2) -
D) - 9 FEET	R) - 20 FEET	3) -
E) - 10 FEET	S) - 21 FEET	4) -
F) - 11 FEET	T) - 22 FEET	5) -
G) - 12 FEET	U) - 23 FEET	6) -
H) - 13 FEET	V) - 24 FEET	7) -
J) - 14 FEET	W) - 25 FEET	8) -
K) - 15 FEET	X) - 26 FEET	9) -
L) - 16 FEET	Y) - 27 FEET	0) -

FIFTH CHARACTER - AXLE CONFIGURATION

1 - SEMI TRAILER - SINGLE AXLE
2 - SEMI TRAILER - TANDEM AXLE
3 - SEMI TRAILER - TRI-AXLE
4 - FULL TRAILER - ONE STEERABLE AND ONE TRAILING AXLE
5 - FULL TRAILER - ONE STEERABLE AND TWO TRAILING AXLES

SECOND CHARACTER - PLANT IDENTIFICATION

1 - CANFIELD

Model Year - G model year 9/25/85 pdy per Mr. Williams
First Character

THIRD CHARACTER - ALTERNATE GAWR, TIRE AND RIM INFORMATION

THE THIRD CHARACTER INDICATES ALTERNATE GAWR, TIRE AND RIM INFORMATION, IF SUCH IS LISTED ON THE TRAILER CERTIFICATION PLATE, USING THE CHARACTERS ESTABLISHED IN THE THIRD CHARACTER OF THE SECOND SECTION
A ZERO INDICATES NO ALTERNATE GAWR, TIRE AND RIM INFORMATION.

FOURTH TO EIGHT CHARACTERS - SEQUENTIAL NUMBER

SINCERELY YOURS,

Don Williams

DON WILLIAMS
TRAILEX, INC.

4