

RAM-LIN CUSTOM TRAILERS
9388 SIDNEY HAYES ROAD
ORLANDO FL 32809

PAGE 1

01-22-NIB-2069

7/15/85

ADMINISTRATOR, NATIONAL HIGHWAY
TRAFFIC SAFETY ADMINISTRATION
400 SEVENTH STREET, S.W.
WASHINGTON, DC. 20590
ATTN: VIN COORDINATOR

ORIGINAL

DEAR SIR:

IN COMPLIANCE WITH FEDERAL STANDARD 115 S6.3, THE INFORMATION
NECESSARY TO DECIPHER THE CHARACTERS CONTAINED IN OUR TRAILER
VIN'S FOLLOWS TO BE EFFECTIVE JULY 1, 1986.

THE FIRST SECTION, THE MANUFACTURER IDENTIFIER ASSIGNED TO US BY
THE S.A.E. IS RL1 — 1RL per Craig Corbett 9/30/85 pdy

THE SECOND SECTION OF FIVE CHARACTERS IDENTIFIES THE REQUIRED
ATTRIBUTES OF OUR TRAILERS AS FOLLOWS:

FIRST AND SECOND CHARACTERS - TYPE AND MODEL OF TRAILER

THE FIRST CHARACTER IDENTIFIES THE TRAILER TYPE:

A,B,C,D OR E -- BOAT TRAILER
F,G,H,J OR K -- CARGO/UTILITY TRAILER
L,M OR N -- CAMPER TRAILER
P OR R -- MOTORCYCLE TRAILER
S OR T -- SNOWMOBILE TRAILER
U OR V -- MOBILE EQUIPMENT TRAILER
W,X,Y OR Z -- ANY OTHER SPECIAL PURPOSE TRAILER.

THE FIRST AND SECOND CHARACTERS TOGETHER IDENTIFY THE
SPECIFIC MODEL OF OUR TRAILERS AS FOLLOWS:

MODEL	CHARACTERS	MODEL	CHARACTERS
DESIGNATION	1 AND 2	DESIGNATION	1 AND 2
512	A B	52	A C
725	A F	925	A H
203	A J	214	A K
234	A M	266	A P
83	A S	835	A U
288	A V	2235	A W
307	A X	3510	A Y
82U	F B	625U	F C
825U	F D	1225U	F E
166U	F F	206U	F G
83U	F H	612U	F J

MODEL	CHARACTERS	MODEL	CHARACTERS
DESIGNATION	1 AND 2	DESIGNATION	1 AND 2

THIRD CHARACTER - GAWR, TIRE AND RIM INFORMATION

THE STANDARD GAWR, TIRE AND RIM INFORMATION OF OUR TRAILERS IS INDICATED AS FOLLOWS:

A - GAWR 1560 WITH 4.80-12 B	TIRES 12X4.00	RIMS, AT 60 PSI
B - GAWR 2000 WITH C78-13 B	TIRES 13X5.00	RIMS, AT 32 PSI
C - GAWR 2726 WITH F78-14 B	TIRES 14X6.00	RIMS, AT 32 PSI
D - GAWR 2235 WITH C78-13 B	TIRES 13X5.00	RIMS, AT 32 PSI
E - GAWR 1750 WITH F78-14 B	TIRES 14X6.00	RIMS, AT 32 PSI
F - GAWR 3360 WITH F78-14 STC	TIRES 14X6.00	RIMS, AT 50 PSI
G - GAWR 2000 WITH B78-13 B	TIRES 13X5.00	RIMS, AT 32 PSI
H - GAWR 4472 WITH 8-14.5 LTF	TIRES 14.5X6.00	RIMS, AT 100 PSI
J - GAWR 3000 WITH F78-14 STC	TIRES 14X6.00	RIMS, AT 50 PSI
K - GAWR 1750 WITH C78-13 B	TIRES 13X5.00	RIMS, AT 32 PSI
L - GAWR 4545 WITH N78-15 D	TIRES 15X7.00	RIMS, AT 40 PSI
M - GAWR 3333 WITH F78-14 STC	TIRES 14X6.00	RIMS, AT 50 PSI

FOURTH CHARACTER - LENGTH OF TRAILER

TRAILER LENGTHS TO THE NEAREST FOOT ARE CODED AS FOLLOWS:

A) - 6 FEET	M) - 17 FEET	Z) - 28 FEET
B) - 7 FEET	N) - 18 FEET	1) -
C) - 8 FEET	P) - 19 FEET	2) -
D) - 9 FEET	R) - 20 FEET	3) -
E) - 10 FEET	S) - 21 FEET	4) -
F) - 11 FEET	T) - 22 FEET	5) -
G) - 12 FEET	U) - 23 FEET	6) -
H) - 13 FEET	V) - 24 FEET	7) -
J) - 14 FEET	W) - 25 FEET	8) -
K) - 15 FEET	X) - 26 FEET	9) -
L) - 16 FEET	Y) - 27 FEET	0) -

FIFTH CHARACTER - AXLE CONFIGURATION

1 - SEMI TRAILER - SINGLE AXLE
2 - SEMI TRAILER - TANDEM AXLE
3 - SEMI TRAILER - TRI-AXLE
4 - FULL TRAILER - ONE STEERABLE AND ONE TRAILING AXLE
5 - FULL TRAILER - ONE STEERABLE AND TWO TRAILING AXLES

*10th position should be model year 9/30/85
per Craig Corbett*

SECOND CHARACTER - PLANT IDENTIFICATION

1 - ORLANDO

THIRD CHARACTER - ALTERNATE GAWR, TIRE AND RIM INFORMATION

THE THIRD CHARACTER INDICATES ALTERNATE GAWR, TIRE AND RIM INFORMATION, IF SUCH IS LISTED ON THE TRAILER CERTIFICATION PLATE, USING THE CHARACTERS ESTABLISHED IN THE THIRD CHARACTER OF THE SECOND SECTION

A ZERO INDICATES NO ALTERNATE GAWR, TIRE AND RIM INFORMATION.

FOURTH TO EIGHT CHARACTERS - SEQUENTIAL NUMBER

SINCERELY YOURS,

Craig Corbett

CRAIG CORBETT
RAM-LIN CUSTOM TRAILERS