



6


7


8

B 12/16/85 pdf

SKIPPER 'B' TRAILERS,INC.
P.O. BOX 769
JOSHUA TX 76058

ORIGINAL

12/06/85

ADMINISTRATOR, NATIONAL HIGHWAY
TRAFFIC SAFETY ADMINISTRATION
400 SEVENTH STREET, S.W.
WASHINGTON, DC. 20590
ATTN: VIN COORDINATOR

01-22-NHB-2147

DEAR SIR:

IN COMPLIANCE WITH FEDERAL STANDARD 115 S6.3, THE INFORMATION NECESSARY TO DECIPHER THE CHARACTERS CONTAINED IN OUR TRAILER VIN'S FOLLOWS TO BE EFFECTIVE NOVEMBER 1, 1985.

THE FIRST SECTION, THE MANUFACTURER IDENTIFIER ASSIGNED TO US BY THE S.A.E. IS 1SZ.

THE SECOND SECTION OF FIVE CHARACTERS IDENTIFIES THE REQUIRED ATTRIBUTES OF OUR TRAILERS AS FOLLOWS:

FIRST AND SECOND CHARACTERS - TYPE AND MODEL OF TRAILER

THE FIRST CHARACTER IDENTIFIES THE TRAILER TYPE:

A,B,C,D OR E	-- BOAT TRAILER
F,G,H,J OR K	-- CARGO/UTILITY TRAILER
L,M OR N	-- CAMPER TRAILER
P OR R	-- MOTORCYCLE TRAILER
S OR T	-- SNOWMOBILE TRAILER
U OR V	-- MOBILE EQUIPMENT TRAILER
W,X,Y OR Z	-- ANY OTHER SPECIAL PURPOSE TRAILER.

THE FIRST AND SECOND CHARACTERS TOGETHER IDENTIFY THE SPECIFIC MODEL OF OUR TRAILERS AS FOLLOWS:

MODEL DESIGNATION	CHARACTERS 1 AND 2		MODEL DESIGNATION	CHARACTERS 1 AND 2	
340	A	A	640	A	B
840	A	C	948	A	D
1048	A	E	1248	A	F
956	A	G	1256	A	H
1760	A	I	1960	A	J
2160	A	K	1976	A	L
2576	A	M	3476T	A	N
4376T	A	O	5376T	A	P
6076T	A	Q	GLT14	A	R
GLT16	A	S	CAT 14	A	T
CAT 18	A	U	P2024	A	V

MODEL DESIGNATION	CHARACTERS 1 AND 2	MODEL DESIGNATION	CHARACTERS 1 AND 2
P2024T	AW	P2028T	AX
1761	BA	1766	BB
1773	BC	1780	BD
1980	BE	1980T	BF
2180T	BG	2580T	BH
1980	BU	1820	CA
1924	CB	1924OR	CC
1928	CD	1928OR	CE
2124	CF	2128	CG
2132	CH	2140T	CI

THIRD CHARACTER - GAWR, TIRE AND RIM INFORMATION

THE STANDARD GAWR, TIRE AND RIM INFORMATION OF OUR TRAILERS IS INDICATED AS FOLLOWS:

A - GAWR 780 WITH 4.80-8 A	TIRES 8X3.75	RIMS, AT	30 PSI
B - GAWR 1080 WITH 4.80-8 B	TIRES 8X3.75	RIMS, AT	60 PSI
C - GAWR 1560 WITH 4.80-12 B	TIRES 12X3.75	RIMS, AT	55 PSI
D - GAWR 1680 WITH 5.30-12 B	TIRES 12X4.25	RIMS, AT	55 PSI
E - GAWR 2130 WITH B78-13 STB	TIRES 13X4.50	RIMS, AT	35 PSI
F - GAWR 2630 WITH B78-13 STC	TIRES 13X4.50	RIMS, AT	50 PSI
G - GAWR 3420 WITH F78-14 STC	TIRES 14X5.50	RIMS, AT	50 PSI
H - GAWR 3730 WITH G78-14 STC	TIRES 14X5.50	RIMS, AT	50 PSI
J - GAWR 4080 WITH 7.00-15 LTD	TIRES 15X5.50	RIMS, AT	60 PSI
K - GAWR 1810 WITH 20.5X8.0-10 B	TIRES 10X6.00	RIMS, AT	35 PSI
L - GAWR 2210 WITH 20.5X8.0-10 C	TIRES 10X6.00	RIMS, AT	50 PSI

FOURTH CHARACTER - LENGTH OF TRAILER

TRAILER LENGTHS TO THE NEAREST FOOT ARE CODED AS FOLLOWS:

A) - 6 FEET	M) - 17 FEET	Z) - 28 FEET
B) - 7 FEET	N) - 18 FEET	1) -
C) - 8 FEET	P) - 19 FEET	2) - 30 FEET
D) - 9 FEET	R) - 20 FEET	3) -
E) - 10 FEET	S) - 21 FEET	4) -
F) - 11 FEET	T) - 22 FEET	5) -
G) - 12 FEET	U) - 23 FEET	6) -
H) - 13 FEET	V) - 24 FEET	7) -
J) - 14 FEET	W) - 25 FEET	8) -
K) - 15 FEET	X) - 26 FEET	9) -
L) - 16 FEET	Y) - 27 FEET	0) -

FIFTH CHARACTER - AXLE CONFIGURATION

1 - SEMI TRAILER - SINGLE AXLE
2 - SEMI TRAILER - TANDEM AXLE
3 - SEMI TRAILER - TRI-AXLE