SND BIRD TRAILER CO., INC.
P. 0. BOX 30
IRON BIDGE, WI 53035
- 2527

07/16/83

5/10/84 EW

ADMINISTRATOR, NATIONAL HIGHWAY TRAFFIC SAFETY ADMINISTRATION 400 SEVENTH STREET, S.W.

WASHINGTON, DC. 20590

ATTN: VIN COORDINATOR

ORIGINAL

488

DEAR SIR:

IN COMPLIANCE WITH FEDERAL STANDARD 115 S6.3, THE INFORMATION NECESSARY TO DECIPHER THE CHARACTERS CONTAINED IN OUR TRAILER VIN\*S FOLLOWS TO BE EFFECTIVE JULY 16, 1984.

THE FIRST SECTION. THE MANUFACTURER IDENTIFIER ASSIGNED TO US BY THE SAE. IS 185.

THE SECOND SECTION OF 5 CHARACTERS IDENTIFIES THE REQUIRED ATTRIBUTES OF OUR TRAILERS AS FOLLOWS:

IST AND 2ND CHARACTERS - TYPE AND MODEL OF TRAILER

THE 1ST CHARACTER IDENTIFIES THE TRAILER TYPE. LETTERS A.
B.C.D OR E IDENTIFY A BOAT TRAILER. LETTERS F.G.H.J OR K
IDENTIFY A CARGO/UTILITY TRAILER. LETTERS L.M OR N IDENTIFY
A CAMPER TRAILER. LETTERS P OR R IDENTIFY A MOTORCYCLE
TRAILER. LETTERS S OR T IDENTIFY A SNOWMOBILE TRAILER.
LETTERS U.Y IDENTIFY A MOBILE EQUIPMENT TRAILER. LETTERS
W.X.Y OR Z IDENTIFY AN OTHER SPECIAL PURPOSE TRAILER.

THE 1ST AND 2ND CHARACTERS TOGETHER IDENTIFY THE SPECIFIC MODEL OF OUR TRAILERS AS FOLLOWS:

MODEL	CHARACTERS	MODEL	CHARACTERS	
DESIGNATION	1 AND 2	DESIGNATION	1 AND 2	
8-12	A 1	8-14	A 2	person
8-800	A 3	B-16	A 4	<b>-</b>
8-17	A 5	B-19	A 6	喜 喜
C-18	A 7	VB-17	B 1	
VB-20	B 2	BR-18	B 3	
00-12	C 1	DO-15	C 2	DEFECTS - S
D0-20	C 3	DO-25	C 4	
R-5614	D 1	R-6620	D 2	A B
U-10	F 1	AT-10	F 2	€3
3P-12	S 5	4P-SB	T 4	<u> </u>
BR-20	B 5	C-18	A 8	<b>a</b> 8
BR-17	B 4	PT-1817	B 9	
PT-2435 T	B 0	1P	S 1	
2P	S 2	2P-90	S 3	
2P-10	S 4	3P-12-2	T 1	
3PSB-12-2	T 2	4P	T 3	
6PSB	7 6			•

#### 3RD CHARACTER - GAWR, TIRE AND RIM INFORMATION

## THE STANDARD GAWR, TIRE AND RIM INFORMATION OF OUR TRAILERS IS INDICATED AS FOLLOWS:

```
A - GAWR 780 WITH 4.80-8A
                                       TIRES 8X4.50
                                                          RIMS AT 30 PSI
 B - GAWR 1180 WITH 4-80-88
                                     TIRES 8X4.50
                                                          RIMS AT 60 PSI
 C - GAWR 1430 WITH 5.70-8B
                                     TIRES 8X4.50
                                                          RINS AT 50 PSI
 D - GAWR 1820 WITH 5.70-80
                                     TIRES 8X4.50
                                                          RIMS AT 75 PSI
 E - GAWR 1540 WITH 18.5X8.5-8 B TIRES 8X7.00
                                                          RIMS AT 35 PSI
 F - GAWR 1880 WITH 18.5X8.5-8C TIRES 8X7.00
                                                          RIMS AT 50 PSI
G - GAWR 1810 WITH 20.5X8.0-10B TIRES 10X6.00
                                                          RIMS AT 35 PSI
H - GAWR 2210 WITH 20.5X8.0-10C TIRES 10X6.00
                                                          RIMS AT 50 PSI
J - GAWR 2660 WITH 20.5X8.0-100 TIRES 10X6.00
                                                          RIMS AT 70 PSI
K - GAWR 1560 WITH 4.80-12 B TIRES 12X4.00
                                                          RIMS AT 60 PSI
L - GAWR 1980 WITH 4.80-12C TIRES 12X4.00
M - GAWR 1680 WITH 5.30-12B TIRES 12X4.00
                                                          RIMS AT 90 PSI
M - GAWR 1680 WITH 5.30-12 C TIRES 12X4.00 RIMS AT 80 PSI
P - GAWR 2100 WITH B78-13 B TIRES 13X5.00 RIMS AT 32 PSI
R - GAWR 2630 WITH B78-13ST C TIRES 13X5.00
                                                         RIMS AT50 PSI
S - GAWR 2640 WITH D78-14 B TIRES 14X6.00 RIMS AT 32 PSI
T - GAWR 3240 WITH G78-14 B TIRES 14X6.00 RIMS AT 32 PSI
U - GAWR 3940 WITH L78-15 B TIRES 14X6.00 RIMS AT 32 PSI
V - GANR 1240 WITH 16.5X6.5-8 B TIRES 8X7.00
                                                        RIMS AT 45 PSI
```

# 4TH CHARACTER - LENGTH OF TRAILER TRAILER LENGTHS TO THE NEAREST FOOT ARE CODED AS FOLLOWS:

```
A) - 6 FEET
                M) - 17 FEET
                                  Z) - 28 FEET
B) - 7 "
                N) - 18
                                 1) - 35 "
C) - 8 "
                PI - 19
                         77
                                  2) -
0) - 9 "
                R) - 20
                                  3) -
E) - 10 "
                 S) - 21 "
                                  4) -
F) - 11 "
                 T) - 22
61 - 12
        11
                 U1 - 23
H1 - 13
                V) - 24
J) - 14 "
                 W) - 25
K) - 15
        **
                 X1 - 26
L) - 16
                Y1 - 27
```

### 5TH CHARACTER - AXLE CONFIGURATION

- 1 SEMI TRAILER SINGLE AXLE
- 2 SEMI TRAILER TANDEM AXLE
- 3 SEMI TRAILER TRI-AXLE
- 4 FULL TRAILER DNE STEERABLE AND DNE TRAILING AXLE
- 5 FULL TRAILER ONE STEERABLE AND TWO TRAILING AXLES

### PAGE 3

THE THIRD SECTION CONTAINS THE FOLLOWING SPECIAL INFORMATION:

IST CHARACTER - MODEL YEAR PER TABLE II FEDERAL STANDARD 115

2ND CHARACTER - PLANT IDENTIFICATION

1 - IRON RIDGE, WI

3RD CHARACTER - ALTERNATE GAWR, TIRE AND RIM INFORMATION

THE 3RD CHARACTER INDICATES ALTERNATE GAWR, TIRE AND RIM INFORMATION, IF SUCH IS LISTED ON THE TRAILER CERTIFICATION PLATE, USING THE CHARACTERS ESTABLISHED IN THE 3RD CHARACTER OF THE SECOND SECTION.

A ZERO INDICATES NO ALTERNATE GAWR, TIRE AND RIM INFORMATION.

4TH - 8TH CHARACTERS - SEQUENTIAL NUMBER

SINCERELY YOURS,

PETE DECHSNER
SNO BIRD TRAILER CO., INC.