

SUPERTRAIL MFG. CO. INC.
P. O. BOX 116
ABERDEEN MS 39730

ORIGINAL

9/20/88

ADMINISTRATOR, NATIONAL HIGHWAY
TRAFFIC SAFETY ADMINISTRATION
400 SEVENTH STREET, S.W.
WASHINGTON, DC. 20590
ATTN: VIN COORDINATOR

01-22-N11B-3150

3 pgs.

DEAR SIR:

IN COMPLIANCE WITH FEDERAL STANDARD 115 S6.3, THE INFORMATION
NECESSARY TO DECIPHER THE CHARACTERS CONTAINED IN OUR TRAILER
VIN'S FOLLOWS TO BE EFFECTIVE OCTOBER 1, 1988.

THE FIRST SECTION, THE MANUFACTURER IDENTIFIER(S) ASSIGNED TO US BY
THE S. A. E. - 45D

THE SECOND SECTION OF FIVE CHARACTERS IDENTIFIES THE REQUIRED
ATTRIBUTES OF OUR TRAILERS AS FOLLOWS:

FIRST AND SECOND CHARACTERS - TYPE AND MODEL OF TRAILER

THE FIRST CHARACTER IDENTIFIES THE TRAILER TYPE:

- A, B, C, D OR E -- BOAT TRAILER
- F, G, H, J OR K -- CARGO/UTILITY TRAILER
- L, M OR N -- CAMPER TRAILER
- P OR R -- MOTORCYCLE TRAILER
- S OR T -- SNOWMOBILE TRAILER
- V OR V -- MOBILE EQUIPMENT TRAILER
- W, X, Y OR Z -- ANY OTHER SPECIAL PURPOSE TRAILER.

THE FIRST AND SECOND CHARACTERS TOGETHER IDENTIFY THE
SPECIFIC MODEL OF OUR TRAILERS AS FOLLOWS:

MODEL DESIGNATION	CHARACTERS 1 AND 2	MODEL DESIGNATION	CHARACTERS 1 AND 2
F-3-8	B 1	F-3-12	B 2
F-3-13	B 3	P-4-10	B 4
V-3-13	B 5	V-4-14	B 6

THIRD CHARACTER - GAWR, TIRE AND RIM INFORMATION

THE STANDARD GAWR, TIRE AND RIM INFORMATION OF OUR TRAILERS IS INDICATED AS FOLLOWS:

A - GAWR 800 WITH 4.80-8 B	TIRES 8X3.75	RIMS, AT 60 PSI
B - GAWR 1100 WITH 4.80-12 B	TIRES 12X4.00	RIMS, AT 60 PSI
C - GAWR 1700 WITH B78-13 STB	TIRES 13X4.50	RIMS, AT 35 PSI
D - GAWR 2500 WITH E78-14 B	TIRES 14X6.00	RIMS, AT 32 PSI
E - GAWR 2500 WITH 20.5X8.0-10 D	TIRES 10X6.00	RIMS, AT 75 PSI

FOURTH CHARACTER - LENGTH OF TRAILER

TRAILER LENGTHS TO THE NEAREST FOOT ARE CODED AS FOLLOWS:

A) - 6 FEET	M) - 17 FEET	Z) - 28 FEET
B) - 7 FEET	N) - 18 FEET	1) -
C) - 8 FEET	P) - 19 FEET	2) -
D) - 9 FEET	R) - 20 FEET	3) -
E) - 10 FEET	S) - 21 FEET	4) -
F) - 11 FEET	T) - 22 FEET	5) -
G) - 12 FEET	U) - 23 FEET	6) -
H) - 13 FEET	V) - 24 FEET	7) -
J) - 14 FEET	W) - 25 FEET	8) -
K) - 15 FEET	X) - 26 FEET	9) -
L) - 16 FEET	Y) - 27 FEET	0) -

FIFTH CHARACTER - AXLE CONFIGURATION

1 - SEMI TRAILER - SINGLE AXLE
 2 - SEMI TRAILER - TANDEM AXLE
 3 - SEMI TRAILER - TRI-AXLE
 4 - FULL TRAILER - ONE STEERABLE AND ONE TRAILING AXLE
 5 - FULL TRAILER - ONE STEERABLE AND TWO TRAILING AXLES

3rd position = check digit 11/23 rdef

THE THIRD SECTION CONTAINS THE FOLLOWING SPECIAL INFORMATION:

FIRST CHARACTER - MODEL YEAR PER TABLE II FEDERAL STANDARDS 115

SECOND CHARACTER - PLANT IDENTIFICATION


1 - ABERDEEN

THIRD CHARACTER - ALTERNATE GAWR, TIRE AND RIM INFORMATION

THE THIRD CHARACTER INDICATES ALTERNATE GAWR, TIRE AND RIM INFORMATION, IF SUCH IS LISTED ON THE TRAILER CERTIFICATION PLATE, USING THE CHARACTERS ESTABLISHED IN THE THIRD CHARACTER OF THE SECOND SECTION
A ZERO INDICATES NO ALTERNATE GAWR, TIRE AND RIM INFORMATION.

FOURTH TO EIGHT CHARACTERS - SEQUENTIAL NUMBER

SINCERELY YOURS,



JIMMY A. BELK
SUPERTRAIL MFG. CO. INC.