B 2/12/90 pdg

TRAILEX, INC.
60 INDUSTRIAL PARK DR.
CANFIELD OH 44406

01-22-N11B-3578

4 Pgs.

11/30/89

ADMINISTRATOR, NATIONAL HIGHWAY
TRAFFIC SAFETY ADMINISTRATION
400 SEVENTH STREET, S.W.
WASHINGTON, DC. 20590
ATTN: VIN COORDINATOR

ORIGINAL

DEAR SIR:

IN COMPLIANCE WITH FEDERAL STANDARD 115 S6.3, THE INFORMATION NECESSARY TO DECIPHER THE CHARACTERS CONTAINED IN OUR TRAILER VIN'S FOLLOWS TO BE EFFECTIVE DECEMBER 1, 1989.

THE FIRST SECTION, THE MANUFACTURER IDENTIFIER(S) ASSIGNED TO US BY THE S.A.E. - 1XT

THE SECOND SECTION OF FIVE CHARACTERS IDENTIFIES THE REQUIRED ATTRIBUTES OF OUR TRAILERS AS FOLLOWS:

FIRST AND SECOND CHARACTERS - TYPE AND MODEL OF TRAILER

THE FIRST CHARACTER IDENTIFIES THE TRAILER TYPE:

A, B, C, D OR E -- BOAT TRAILER
F, G, H, J OR K -- CARGO/UTILITY TRAILER
L, M OR N -- CAMPER TRAILER
P OR R -- MOTORCYCLE TRAILER
S OR T -- SNOWMOBILE TRAILER
U OR V -- MOBILE EQUIPMENT TRAILER
W, X, Y OR Z -- ANY OTHER SPECIAL PURPOSE TRAILER.

THE FIRST AND SECOND CHARACTERS TOGETHER IDENTIFY THE SPECIFIC MODEL OF OUR TRAILERS AS FOLLOWS:

MODEL DESIGNATION	CHARACTERS 1 AND 2		MODEL DESIGNATION	CHARACTERS 1 AND 2	
200	A	A	400	A	B
400	A	C	405 W.T.	A	D
405W.T.	A	E	405A-16	A	F
400FSC	A	G	500	A	H
500	A	J	505	A	K
505	A	L	700	A	M
70DD/CB	A	N	700SCC	A	P
700ECC	A	R	850	A	S
900	A	T	1100	A	U
1400	A	V	1700	A	W
1700TD	A	X	1700TD	A	Y

1

MODEL DESIGNATION	CHARACTERS 1 AND 2		MODEL DESIGNATION	CHARACTERS 1 AND 2	
2000SA	A	Z	400HC-14	B	A
400HC-16	B	B	6000PRA	B	C
400HC-16	B	D	400HC-18	B	F
400HC-18	B	G	400SC-20	B	H
2400STIL	B	J	UT-2100	B	M
2420 RA	B	N	2920 RA	B	P
41002RA	B	R	1200WV	B	S
1100HC21	B	T	6000-2A	C	A
4100A	C	B	3000SA-A	C	C
3000A	C	D	2400A	C	E
2400A	C	F	2000A	C	G
2000A	C	H	1700A	C	J
1100A	C	K	2000	D	A
2000	D	B	2000PY23	D	C
2400	D	E	2400	D	F
3000SA	D	G	3000	D	H
4100-2X	D	J	4100-3X	D	K
6000X2X	D	L	8500-3X	D	M
2100	E	A	2400T	E	B
2600T	E	C	2700	E	D
2900	E	E	3300T	E	F
1200	E	G	9000	E	H
400HC-UL	E	J	400 UL	E	K
33002RA	E	P	1418 RA	E	R
1718 RA	E	S	916	E	T
1116	E	U	416HC-16	E	V
416HC-16	E	W	418HC-18	E	X
418HC-18	E	Y	6522 TS	F	A
7022TSII	F	B	7522TSII	F	C
7724 TS	F	D	7726TSII	F	E
UT1500LG	F	F	UT2400LG	F	G
UT4800LG	F	H	1682TB	G	B
850C	P	A	800X34	S	A
800X44	S	B	800X72	S	C
800X86BW	S	D	800X86	S	E
1600X86	S	F	800X51	S	G
800X60	S	H	800X70	S	J
800X86BB	S	K	800X34	T	A
800X44	T	B	800X72	T	C
800X51	T	G	800X60	T	H
60SA	W	A	60	W	B
66	W	C	60HD	W	D
66HD	W	F	66HD/SA	W	G
70SS/SA	W	H	70SS	W	J
6631HS	W	K	7031HS	W	L
7041HS	W	M	7041HSLB	W	N
756HSLB	W	P	756HS	W	R
60SA	X	A	60	X	B
66	X	C	60HD	X	D
66HD	X	E	66HD	X	F
66HD-SA	X	G	70SS-SA	X	H
70SS	X	J	6631-HS	X	K

MODEL DESIGNATION	CHARACTERS 1 AND 2		MODEL DESIGNATION	CHARACTERS 1 AND 2	
7031-HS	X	L	7041-HS	X	M
7041HSLB	X	N	756HSLB	X	P
756 HS	X	R	7541-HS	X	S
1000-6	X	T	1000-8	X	U
222	Y	A			

THIRD CHARACTER - GAWR, TIRE AND RIM INFORMATION

THE STANDARD GAWR, TIRE AND RIM INFORMATION OF OUR TRAILERS IS INDICATED AS FOLLOWS:

A - GAWR 500	WITH 4.80-8 A	TIRES 8X3.75	RIMS, AT	30 PSI
B - GAWR 780	WITH 4.80-8 A	TIRES 8X3.75	RIMS, AT	30 PSI
C - GAWR 500	WITH 4.80-8 B	TIRES 8X3.75	RIMS, AT	60 PSI
D - GAWR 1180	WITH 4.80-8 B	TIRES 8X3.75	RIMS, AT	60 PSI
E - GAWR 1430	WITH 5.70-8 D	TIRES 8X4.50	RIMS, AT	50 PSI
F - GAWR 1820	WITH 5.70-8 C	TIRES 8X4.50	RIMS, AT	75 PSI
G - GAWR 1200	WITH 4.80-12 B	TIRES 12X3.75	RIMS, AT	60 PSI
H - GAWR 1560	WITH 4.80-12 B	TIRES 12X3.75	RIMS, AT	60 PSI
J - GAWR 1680	WITH 5.30-12 B	TIRES 12X4.25	RIMS, AT	55 PSI
K - GAWR 2000	WITH 6.50-13 STD	TIRES 13X4.50	RIMS, AT	35 PSI
L - GAWR 2120	WITH 6.50-13 STD	TIRES 13X4.50	RIMS, AT	35 PSI
M - GAWR 2120	WITH 6.50-13 STC	TIRES 13X4.50	RIMS, AT	50 PSI
N - GAWR 2630	WITH 6.50-13 STC	TIRES 13X4.50	RIMS, AT	50 PSI
P - GAWR 3500	WITH 8.55-15 STC	TIRES 15X5.50	RIMS, AT	50 PSI
R - GAWR 1240	WITH 16.5X6.5-8 B	TIRES 8X5.375	RIMS, AT	45 PSI
S - GAWR 2000	WITH 20.5X8.0-10 C	TIRES 10X6.00	RIMS, AT	50 PSI
T - GAWR 2000	WITH 20.5X8.0-10 C	TIRES 10X6.00	RIMS, AT	50 PSI
U - GAWR 2500	WITH 20.5X8.0-10 D	TIRES 10X6.00	RIMS, AT	70 PSI
V - GAWR 5580	WITH 8-14.5 LTF	TIRES 14.5X6.00	RIMS, AT	100 PSI
W - GAWR 2200	WITH D78-13 STC	TIRES 13X4.50	RIMS, AT	50 PSI
X - GAWR 3064	WITH P205/75B14	TIRES 14X6.00	RIMS, AT	32 PSI
Y - GAWR 2400	WITH P195/75B14	TIRES 14X5.50	RIMS, AT	32 PSI
Z - GAWR 2000	WITH D78-13 B	TIRES 13X4.50	RIMS, AT	32 PSI
1 - GAWR 1810	WITH 20.5X8.0-10 B	TIRES 10X6.00	RIMS, AT	35 PSI
2 - GAWR 3064	WITH P205/75B14	TIRES 14X5.50	RIMS, AT	32 PSI
3 - GAWR 1880	WITH 18.5X8.5-8 C	TIRES 8X7.00	RIMS, AT	50 PSI

FOURTH CHARACTER - LENGTH OF TRAILER

TRAILER LENGTHS TO THE NEAREST FOOT ARE CODED AS FOLLOWS:

A) - 6 FEET	M) - 17 FEET	Z) - 28 FEET
B) - 7 FEET	N) - 18 FEET	1) -
C) - 8 FEET	P) - 19 FEET	2) -
D) - 9 FEET	R) - 20 FEET	3) -
E) - 10 FEET	S) - 21 FEET	4) -
F) - 11 FEET	T) - 22 FEET	5) -
G) - 12 FEET	U) - 23 FEET	6) -
H) - 13 FEET	V) - 24 FEET	7) -
J) - 14 FEET	W) - 25 FEET	8) -
K) - 15 FEET	X) - 26 FEET	9) -
L) - 16 FEET	Y) - 27 FEET	0) -

FIFTH CHARACTER - AXLE CONFIGURATION

1 - SEMI TRAILER - SINGLE AXLE
2 - SEMI TRAILER - TANDEM AXLE
3 - SEMI TRAILER - TRI-AXLE
4 - FULL TRAILER - ONE STEERABLE AND ONE TRAILING AXLE
5 - FULL TRAILER - ONE STEERABLE AND TWO TRAILING AXLES

9th Character = Check digit

THE THIRD SECTION CONTAINS THE FOLLOWING SPECIAL INFORMATION:

FIRST CHARACTER - MODEL YEAR PER TABLE II FEDERAL STANDARDS 115

SECOND CHARACTER - PLANT IDENTIFICATION

1 - CANFIELD, OH

THIRD CHARACTER - ALTERNATE GAWR, TIRE AND RIM INFORMATION

THE THIRD CHARACTER INDICATES ALTERNATE GAWR, TIRE AND RIM INFORMATION, IF SUCH IS LISTED ON THE TRAILER CERTIFICATION PLATE, USING THE CHARACTERS ESTABLISHED IN THE THIRD CHARACTER OF THE SECOND SECTION
A ZERO INDICATES NO ALTERNATE GAWR, TIRE AND RIM INFORMATION.

FOURTH TO EIGHT CHARACTERS - SEQUENTIAL NUMBER

SINCERELY YOURS,

Don H. Williams
DON WILLIAMS
TRAILEX, INC.