B 11/5/90 pdg

CB

4 pgs

TRAILEX, INC.
60 INDUSTRIAL PARK DR.
CANFIELD OH 44406

ORIGINAL

01-22-N11B-3991

7/09/90

ADMINISTRATOR, NATIONAL HIGHWAY
TRAFFIC SAFETY ADMINISTRATION
400 SEVENTH STREET, S.W.
WASHINGTON, DC. 20590
ATTN: VIN COORDINATOR

DEAR SIR:

IN COMPLIANCE WITH FEDERAL STANDARD 115 S6.3, THE INFORMATION NECESSARY TO DECIPHER THE CHARACTERS CONTAINED IN OUR TRAILER VIN'S FOLLOWS TO BE EFFECTIVE AUGUST 1, 1990.

THE FIRST SECTION, THE MANUFACTURER IDENTIFIER(S) ASSIGNED TO US BY THE S.A.E. - 1XT

THE SECOND SECTION OF FIVE CHARACTERS IDENTIFIES THE REQUIRED ATTRIBUTES OF OUR TRAILERS AS FOLLOWS:

FIRST AND SECOND CHARACTERS - TYPE AND MODEL OF TRAILER

THE FIRST CHARACTER IDENTIFIES THE TRAILER TYPE:

A, B, C, D OR E -- BOAT TRAILER
F, G, H, J OR K -- CARGO/UTILITY TRAILER
L, M OR N -- CAMPER TRAILER
P OR R -- MOTORCYCLE TRAILER
S OR T -- SNOWMOBILE TRAILER
U OR V -- MOBILE EQUIPMENT TRAILER
W, X, Y OR Z -- ANY OTHER SPECIAL PURPOSE TRAILER.

RECEIVED
NHTSA DOCKET
91 APR 2 AM 11:21

THE FIRST AND SECOND CHARACTERS TOGETHER IDENTIFY THE SPECIFIC MODEL OF OUR TRAILERS AS FOLLOWS:

MODEL DESIGNATION	CHARACTERS 1 AND 2		MODEL DESIGNATION	CHARACTERS 1 AND 2	
200	A	A	400	A	B
400	A	C	405 W.T.	A	D
405W.T.	A	E	405A-16	A	F
400FSC	A	G	500	A	H
500	A	J	505	A	K
505	A	L	700	A	M
70DD/CB	A	N	700SCC	A	P
700ECC	A	R	850	A	S
900	A	T	1100	A	U
1400	A	V	1700	A	W
1700TD	A	X	1700TD	A	Y

MODEL DESIGNATION	CHARACTERS 1 AND 2		MODEL DESIGNATION	CHARACTERS 1 AND 2	
2000SA	A	Z	400HC-14	B	A
400HC-16	B	B	60002RA	B	C
400HC-16	B	D	400HC-18	B	F
400HC-18	B	G	400SC-20	B	H
2400STIL	B	J	UT-2100	B	M
2420 RA	B	N	2920 RA	B	P
41002RA	B	R	1200WV	B	S
1100HC21	B	T	6000-2A	C	A
4100A	C	B	3000SA-A	C	C
3000A	C	D	2400A	C	E
2400A	C	F	2000A	C	G
2000A	C	H	1700A	C	J
1100A	C	K	2000	D	A
2000	D	B	2000PY23	D	C
2400	D	E	2400	D	F
3000SA	D	G	3000	D	H
4100-2X	D	J	4100-3X	D	K
6000-2X	D	L	8500-3X	D	M
2100	E	A	2400T	E	B
2600T	E	C	2700	E	D
2900	E	E	3300T	E	F
1200	E	G	9000	E	H
400HC-UL	E	J	400 UL	E	K
33002RA	E	P	1418 RA	E	R
1718 RA	E	S	916	E	T
1116	E	U	416HC-16	E	V
416HC-16	E	W	418HC-18	E	X
418HC-18	E	Y	6522 TS	F	A
7022TSII	F	B	7522TSII	F	C
7724 TS	F	D	7726TSII	F	E
UT1500LG	F	F	UT2400LG	F	G
UT4800LG	F	H	1682TB	G	B
850C	P	A	800X34	S	A
800X44	S	B	800X72	S	C
800X86BW	S	D	800X86	S	E
1600X86	S	F	800X51	S	G
800X60	S	H	800X70	S	J
800X86BB	S	K	800X34	T	A
800X44	T	B	800X72	T	C
800X51	T	G	800X60	T	H
60SA	W	A	60	W	B
66	W	C	60HD	W	D
66HD	W	F	66HD/SA	W	G
70SS/SA	W	H	70SS	W	J
6631HS	W	K	7031HS	W	L
7041HS	W	M	7041HSLB	W	N
756HSLB	W	P	756HS	W	R
60SA	X	A	60	X	B
66	X	C	60HD	X	D
66HD	X	E	66HD	X	F
66HD-SA	X	G	70SS-SA	X	H
70SS	X	J	6631-HS	X	K

MODEL DESIGNATION	CHARACTERS 1 AND 2		MODEL DESIGNATION	CHARACTERS 1 AND 2	
7031-HS	X	L	7041-HS	X	M
7041HSLB	X	N	756HSLB	X	P
756 HS	X	R	7541-HS	X	S
1000-6	X	T	1000-8	X	U
222	Y	A			

THIRD CHARACTER - GAWR, TIRE AND RIM INFORMATION

THE STANDARD GAWR, TIRE AND RIM INFORMATION OF OUR TRAILERS IS INDICATED AS FOLLOWS:

A -	GAWR 500	WITH	4.80-8 A	TIRES	8X3.75	RIMS, AT	30	PSI
B -	GAWR 780	WITH	4.80-8 A	TIRES	8X3.75	RIMS, AT	30	PSI
C -	GAWR 500	WITH	4.80-8 B	TIRES	8X3.75	RIMS, AT	60	PSI
D -	GAWR 1180	WITH	4.80-8 B	TIRES	8X3.75	RIMS, AT	60	PSI
E -	GAWR 1430	WITH	5.70-8 B	TIRES	8X4.50	RIMS, AT	50	PSI
F -	GAWR 1820	WITH	5.70-8 C	TIRES	8X4.50	RIMS, AT	75	PSI
G -	GAWR 1200	WITH	4.80-12 B	TIRES	12X3.75	RIMS, AT	60	PSI
H -	GAWR 1560	WITH	4.80-12 B	TIRES	12X3.75	RIMS, AT	60	PSI
J -	GAWR 1680	WITH	5.30-12 B	TIRES	12X4.25	RIMS, AT	55	PSI
K -	GAWR 2000	WITH	6.50-13 STB	TIRES	13X4.50	RIMS, AT	35	PSI
L -	GAWR 2120	WITH	6.50-13 STB	TIRES	13X4.50	RIMS, AT	35	PSI
M -	GAWR 2120	WITH	6.50-13 STC	TIRES	13X4.50	RIMS, AT	50	PSI
N -	GAWR 2630	WITH	6.50-13 STC	TIRES	13X4.50	RIMS, AT	50	PSI
P -	GAWR 3500	WITH	8.55-15 STC	TIRES	15X5.50	RIMS, AT	50	PSI
R -	GAWR 1240	WITH	16.5X6.5-8 B	TIRES	8X5.375	RIMS, AT	45	PSI
S -	GAWR 2000	WITH	20.5X8.0-10 C	TIRES	10X6.00	RIMS, AT	50	PSI
T -	GAWR 2000	WITH	20.5X8.0-10 C	TIRES	10X6.00	RIMS, AT	50	PSI
U -	GAWR 2500	WITH	20.5X8.0-10 D	TIRES	10X6.00	RIMS, AT	70	PSI
V -	GAWR 5580	WITH	8-14.5 LTF	TIRES	14.5X6.00	RIMS, AT	100	PSI
W -	GAWR 2200	WITH	B78-13 STC	TIRES	13X4.50	RIMS, AT	50	PSI
X -	GAWR 3064	WITH	P205/75B14	TIRES	14X6.00	RIMS, AT	32	PSI
Y -	GAWR 2400	WITH	P195/75B14	TIRES	14X5.50	RIMS, AT	32	PSI
Z -	GAWR 2000	WITH	B78-13 B	TIRES	13X4.50	RIMS, AT	32	PSI
1 -	GAWR 1810	WITH	20.5X8.0-10 B	TIRES	10X6.00	RIMS, AT	35	PSI
2 -	GAWR 3064	WITH	P205/75B14	TIRES	14X5.50	RIMS, AT	32	PSI
3 -	GAWR 1880	WITH	18.5X8.5-8 C	TIRES	8X7.00	RIMS, AT	50	PSI

FOURTH CHARACTER - LENGTH OF TRAILER

TRAILER LENGTHS TO THE NEAREST FOOT ARE CODED AS FOLLOWS:

A) - 6 FEET	M) - 17 FEET	Z) - 28 FEET
B) - 7 FEET	N) - 18 FEET	1) -
C) - 8 FEET	P) - 19 FEET	2) -
D) - 9 FEET	R) - 20 FEET	3) -
E) - 10 FEET	S) - 21 FEET	4) -
F) - 11 FEET	T) - 22 FEET	5) -
G) - 12 FEET	U) - 23 FEET	6) -
H) - 13 FEET	V) - 24 FEET	7) -
J) - 14 FEET	W) - 25 FEET	8) -
K) - 15 FEET	X) - 26 FEET	9) -
L) - 16 FEET	Y) - 27 FEET	0) -

FIFTH CHARACTER - AXLE CONFIGURATION

1 - SEMI TRAILER - SINGLE AXLE
2 - SEMI TRAILER - TANDEM AXLE
3 - SEMI TRAILER - TRI-AXLE
4 - FULL TRAILER - ONE STEERABLE AND ONE TRAILING AXLE
5 - FULL TRAILER - ONE STEERABLE AND TWO TRAILING AXLES

9th position = Check Digit

THE THIRD SECTION CONTAINS THE FOLLOWING SPECIAL INFORMATION:

FIRST CHARACTER - MODEL YEAR PER TABLE II FEDERAL STANDARDS 115

SECOND CHARACTER - PLANT IDENTIFICATION

1 - CANFIELD, OH

THIRD CHARACTER - ALTERNATE GAWR, TIRE AND RIM INFORMATION

THE THIRD CHARACTER INDICATES ALTERNATE GAWR, TIRE AND RIM INFORMATION, IF SUCH IS LISTED ON THE TRAILER CERTIFICATION PLATE, USING THE CHARACTERS ESTABLISHED IN THE THIRD CHARACTER OF THE SECOND SECTION
A ZERO INDICATES NO ALTERNATE GAWR, TIRE AND RIM INFORMATION.

FOURTH TO EIGHT CHARACTERS - SEQUENTIAL NUMBER

SINCERELY YOURS,

Don Williams

DON WILLIAMS
TRAILEX, INC.