

ORG5837

ORG5837

1230 Monroe Ave - PO Box 54 - Norfolk, NE 68701 - Phone: 402/371-9430 - Fax: 402/371-5137 - Email: akarkfeld@arkfelds.com

PART 565, VIN DECIPHERING SUBMISSION - TRAILERS (UPDATED April 2010)

VIN POSITION:	DESCRIPTION:	CODES:
1, 2, & 3	WMI (assigned by SAE)	1-A-9
4	Trailer Type	B = Ball Type Pull G = Gooseneck Type Pull 5 = 5th Wheel Type Pull P = Pintle Type Pull
5	Body Type	E = Enclosed or Van Body F = Flatbed H = Hybrid Flatbed/Enclosed L = Flatbed with Lifting Body A = Armored Lifting Body
6 & 7	Length of Trailer (all lengths rounded to nearest foot)	06 = 6 Feet Long 08 = 8 Feet Long 10 = 10 Feet Long 12 = 12 Feet Long 14 = 14 Feet Long 16 = 16 Feet Long 18 = 18 Feet Long 20 = 20 Feet Long 21 = 21 Feet Long 22 = 22 Feet Long 24 = 24 Feet Long 26 = 26 Feet Long 28 = 28 Feet Long 30 = 30 Feet Long
8	Number of Axles	1 = 1 Axle 2 = 2 Axles 3 = 3 Axles
9	Check Digit	See 49 CFR 565.4
10	Model Year	7 = 2007 8 = 2008 9 = 2009 A = 2010 B = 2011 C = 2012
11	Plant Location	N = Norfolk C = Columbus O = Omaha
12, 13, & 14	WMI	7-4-8
15, 16, & 17	Sequential Production Number	001 002



1230 Monroe Ave - PO Box 54 - Norfolk, NE 68701 - Phone: 402/371-9430 - Fax: 402/371-5137 - Email: akarkfeld@arkfelds.com

PART 566, MANUFACTURER IDENTIFICATION SUBMISSION

**Arkfeld Mfg. & Distr. Co., Inc.
Dbal Arkfeld Industries, Inc.
1230 Monroe Ave
PO Box 54
Norfolk, NE 68701
Phone: (402)371-9430
Fax: (402)371-5137
Email: akarkfeld@arkfelds.com**

OWNER OF BOTH COMPANIES: Robert J. Arkfeld

CITY OF INCORPORATION: Arkfeld Mfg. & Distr. Co., Inc., and Arkfeld Industries, Inc. are both incorporated in Norfolk, NE USA

PRODUCT MANUFACTURED: The Arkfeld group of companies builds custom use, flatbed, enclosed, hybrid (50/50 flatbed/enclosed) trailers. Some are equipped with hydraulic telescoping scissor lifting arms.

These trailers are built from steel, stainless steel, aluminum, and bullet-resistant materials for armored applications. Trailers may have single, dual, or triple axles, have ball-pull, gooseneck-pull, fifth wheel-pull, or pintle style hitches. Some may include outriggers for stabilization when parked. Trailers can be 6-feet to 30-feet in overall length depending upon application.

Trailers may also include water treatment equipment, solar, wind, and/or hydrogen-assisted gasoline and/or diesel power generators to run installed electrical equipment.

GVWR: The gross vehicle weight ratings (GVWR) of our products can range from 350-lbs. to 26,000-lbs.

SIGNED: Robert J. Arkfeld

DATE: 05/05/2010