

ORG 7985

VIN DECIPHERING-HARD HAT TRAILERS LLC

1H9/614

| | | |
|--------------------|-----|-------------------|
| 1st Section | | |
| Position 1 | WMI | 1-Assigned by SAE |
| Position 2 | WMI | H-Assigned by SAE |
| Position 3 | WMI | 9-Assigned by SAE |

| | | |
|--------------------|--------------------|------------------------|
| 2nd Section | | |
| Position 4 | Make | H=Hard Hat Trailers |
| Position 5 | Type of trailer | 1=Ball Type pull |
| | | 2=Pinle Hitch |
| | | 3=Gooseneck |
| | | 4=Dolly Hitch |
| | | 5=Fifth Wheel |
| | | 6=Kingpin |
| Position 6 | Body Type | A=Snowmobile Trailer |
| | | B=Boat Trailer |
| | | C=Car Hauler Trailer |
| | | D=Dump Trailer |
| | | E=Enclosed Trailer |
| | | F=Flatbed Trailer |
| | | G=Curtain Side Trailer |
| | | M=Motorcycle Trailer |
| | | N=Livestock trailer |
| | | U=Utility Trailer |
| Position 7 | Length | W=Landscape Trailer |
| | | 4=4 feet |
| | | 5=5 feet |
| | | 6=6feet |
| | | 7=7 feet |
| | | 8=8 feet |
| | | 9=9 feet |
| | | A=10 feet |
| | | B=12 feet |
| | | C=14 feet |
| | | D=16 feet |
| | | E=18 feet |
| | | F=20 feet |
| | | G=22 feet |
| | | H=24 feet |
| Position 8 | Axel Configuration | 1- Single Axles |
| | | 2= 2 Axles |
| | | 3=3 Axles |

| | | |
|--------------------|--------------|-------------------------------|
| 3rd Section | | |
| Position 9 | Check Didget | Calculated See 49 CFR 565.15© |

| | | |
|--------------------|-----------------------|-----------------------|
| 4th Section | | |
| Position 10 | Model Year | C=2012 |
| | | D=2013 |
| | | E=2014 |
| | | F=2015 |
| Position 11 | Plant of Manufacturer | A=Alliance, OH USA |
| Position 12 | WMI | 6- Assigned by SAE |
| Position 13 | WMI | 1- Assigned by SAE |
| Position 14 | WMI | 4- Assigned by SAE |
| Position 15 | | Sequentially Assigned |
| Position 16 | | Sequentially Assigned |
| Position 17 | | Sequentially Assigned |