



105 School House Road  
Cheshire, CT 06410  
U.S.A.

**MANUFACTURER OF OUTDOOR POWER EQUIPMENT**

Products for Turf & Lawncare, Rental, Construction, Nursery, Tree Care, Wood Processing & Farm Industries

11	Plant Location	C = Cheshire, CT USA
12, 13 & 14	WMI	1 7 1 - Assigned by SAE
15, 16 & 17	Sequential Production Number	001 002 003

Please Note: We have added one new piece of equipment. (Model 736K Vacuum)

The revised Certification Label Information and Tire Inflation Pressure Label Information sheets are attached for your records.

President of Company: Salvatore J. Rizzo

City of Incorporation: Cheshire, CT

Products Manufactured: Salsco, Inc. builds Chippers, Strawblowers, Shaving Mills and Leaf Vacuums

GVWR The gross vehicle weight rating (GVWR) of our products from 340-lb Chippers to 15,000-lb Shaving Mills.

Signed:   
Salvatore J. Rizzo, President

Date: 1/17/2014

Toll Free: 800-872-5726  
Phone: 203-271-1682  
Fax: 203-271-2596  
[www.salsco.com](http://www.salsco.com)  
[sales@salsco.com](mailto:sales@salsco.com)

# TIRE INFLATION PRESSURE LABEL

<u>MODEL</u>	<u>FRONT TIRE ORIGINAL SIZE</u>	<u>REAR TIRE ORIGINAL SIZE</u>	<u>SPARE TIRE ORIGINAL SIZE</u>	<u>FRONT TIRE COLD TIRE PRESSURE</u>	<u>REAR TIRE COLD TIRE PRESSURE</u>	<u>SPARE TIRE COLD TIRE PRESSURE</u>	
<b>616 CSV</b>	18.5 X 8.50-8	-	-	50 PSI	-	-	
<b>625NS</b>	ST205/75D14	-	-	50 PSI	-	-	
<b>608B</b>	4.80/400-8	-	-	60 PSI	-	-	
<b>608BE</b>	4.80/400-8	-	-	60 PSI	-	-	
<b>608H</b>	4.80/400-8	-	-	60 PSI	-	-	
<b>609HE</b>	4.80/400-8	-	-	60 PSI	-	-	
<b>610B</b>	4.80/400-8	-	-	60 PSI	-	-	
<b>613H</b>	4.80/400-8	-	-	60 PSI	-	-	
<b>616B</b>	4.80/400-8	-	-	60 PSI	-	-	
<b>616BE</b>	4.80/400-8	-	-	60 PSI	-	-	
<b>413H</b>	18.5 X 8.50-8	-	-	50 PSI	-	-	
<b>416B</b>	18.5 X 8.50-8	-	-	50 PSI	-	-	
<b>8416B</b>	-	ST175/80D13	-	-	50 PSI	-	
<b>8421B</b>	-	ST175/80D13	-	-	50 PSI	-	
<b>8420K</b>	-	ST175/80D13	-	-	50 PSI	-	
<b>8425K</b>	-	ST175/80D13	-	-	50 PSI	-	
<b>8428KAW</b>	-	ST175/80D13	-	-	50 PSI	-	
<b>8625</b>	-	ST205/75D14	-	-	50 PSI	-	
<b>8635K</b>	-	ST205/75D14	-	-	50 PSI	-	
<b>8635Y</b>	-	ST205/75D14	-	-	50 PSI	-	
<b>8635C</b>	-	ST205/75D14	-	-	50 PSI	-	
<b>8635EURO</b>	-	165R/13C	-	-	65 PSI	-	
<b>810</b>	-	ST225/75R15	-	-	65 PSI	-	
<b>810M</b>	-	ST225/75R15	-	-	65 PSI	-	
<b>810MC</b>	-	ST225/75R15	-	-	65 PSI	-	
<b>810XT</b>	-	ST225/75R15	-	-	65 PSI	-	
<b>810PTO</b>	-	ST225/75R15	-	-	65 PSI	-	
<b>813</b>	ST235/80R16	-	ST235/80R16	90 PSI	-	90 PSI	STANDARD TIRE
<b>813</b>	12X16.5LT	-	12X16.5LT	90 PSI	-	90 PSI	WIDE TIRE
<b>813C</b>	215/75R17.5	-	215/75R17.5	125 PSI	-	125 PSI	
<b>813XT</b>	12X16.5LT	-	12X16.5LT	90 PSI	-	90 PSI	WIDE TIRE
<b>813XTC</b>	215/75R17.5	-	215/75R17.5	125 PSI	-	125 PSI	
<b>818</b>	12X16.5LT	12X16.5LT	12X16.5LT	90 PSI	90 PSI	90 PSI	WIDE TIRE
<b>818XT</b>	12X16.5LT	12X16.5LT	12X16.5LT	90 PSI	90 PSI	90 PSI	WIDE TIRE
<b>STRAWBLOWER</b>							
<b>TRAILERED</b>	ST205/75DX14	-	ST205/75DX14	50 PSI	-	50 PSI	
<b>20" SHAVING MILL</b>	ST235/80R16	-	-	80 PSI	-	-	
<b>30" SHAVING MILL</b>	ST225/75R15	ST225/75R15	-	65 PSI	65 PSI	-	
<b>40" SHAVING MILL</b>	ST235/80R16	ST235/80R16	-	65 PSI	65 PSI	-	
<b>725</b>	ST205/75D14	-	-	50 PSI	-	-	
<b>6235B</b>	ST205/75R14	-	-	50 PSI	-	-	
<b>6235BXT</b>	ST205/75R14	-	-	50 PSI	-	-	
<b>736K</b>	ST205/75D14	-	-	50 PSI	-	-	

PRINT DATE 1/17/2014

## CERTIFICATION LABEL

MODEL	MANUFACTURER NAME	DATE OF MFG	GVWR Gross Vehicle Weight Rating	GAWR Gross Axle Weight Rating (front)	GAWR Gross Axle Weight Rating (rear)	Tire Size	Rim Size	Cold Inflation Pressure (single or dual)	Salsco's Compliance Statement	VIN or WMI #	type of vehicle	
616 CSV	SALSCO	To Be Assigned	1,120-lb	1,100-lb	-	18.5 X 8.50-8	8"	50 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER	
625NS	SALSCO	To Be Assigned	1,620-lb	2,200-lb	-	ST205/75D14	14"	50 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER	
608B	SALSCO	To Be Assigned	340-lb	2,000-lb	-	4.80/400-8	8"	60 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER	OVER THE ROAD
608BE	SALSCO	To Be Assigned	340-lb	2,000-lb	-	4.80/400-8	8"	60 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER	OVER THE ROAD
608H	SALSCO	To Be Assigned	340-lb	2,000-lb	-	4.80/400-8	8"	60 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER	OVER THE ROAD
609HE	SALSCO	To Be Assigned	340-lb	2,000-lb	-	4.80/400-8	8"	60 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER	OVER THE ROAD
610B	SALSCO	To Be Assigned	388-lb	2,000-lb	-	4.80/400-8	8"	60 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER	OVER THE ROAD
613H	SALSCO	To Be Assigned	388-lb	2,000-lb	-	4.80/400-8	8"	60 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER	OVER THE ROAD
616B	SALSCO	To Be Assigned	388-lb	2,000-lb	-	4.80/400-8	8"	60 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER	OVER THE ROAD
616BE	SALSCO	To Be Assigned	388-lb	2,000-lb	-	4.80/400-8	8"	60 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER	OVER THE ROAD
413H	SALSCO	To Be Assigned	860-lb	1,100-lb	-	18.5x8.50-8	8"	50 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER	
416B	SALSCO	To Be Assigned	860-lb	1,100-lb	-	18.5x8.50-8	8"	50 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER	
8416B	SALSCO	To Be Assigned	1,420-lb	-	1,800-lb	ST175/80D13	13"	50 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER	
8421B	SALSCO	To Be Assigned	1,420-lb	-	1,800-lb	ST175/80D13	13"	50 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER	
8420K	SALSCO	To Be Assigned	1,420-lb	-	1,800-lb	ST175/80D13	13"	50 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER	
8425K	SALSCO	To Be Assigned	1,420-lb	-	1,800-lb	ST175/80D13	13"	50 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER	

PRINT DATE 1/17/2014

## CERTIFICATION LABEL

MODEL	MANUFACTURER NAME	DATE OF MFG	GVWR Gross Vehicle Weight Rating	GAWR Gross Axle Weight Rating (front)	GAWR Gross Axle Weight Rating (rear)	Tire Size	Rim Size	Cold Inflation Pressure (single or dual)	Salsco's Compliance Statement	VIN or WMI #	type of vehicle
8428KAW	SALSCO	To Be Assigned	1,430-lb	-	1,800-lb	ST175/80D13	13"	50 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER
8625	SALSCO	To Be Assigned	2,120-lb	-	3,500-lb	ST205/75D14	14"	50 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER
8635K	SALSCO	To Be Assigned	2,620-lb	-	3,500-lb	ST205/75D14	14"	50 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER
8635Y	SALSCO	To Be Assigned	2,620-lb	-	3,500-lb	ST205/75D14	14"	50 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER
8635C	SALSCO	To Be Assigned	2,620-lb	-	3,500-lb	ST205/75D14	14"	50 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER
8635EURO	SALSCO	To Be Assigned	2,620-lb	-	2,520-lb	165R/13C	13"	65 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER
810	SALSCO	To Be Assigned	5,000-lb	-	6,000-lb	ST225/75R15	15"	65 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER
810M	SALSCO	To Be Assigned	4,520-lb	-	6,000-lb	ST225/75R15	15"	65 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER
810MC	SALSCO	To Be Assigned	5,000-lb	-	6,000-lb	ST225/75R15	15"	65 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER
810XT	SALSCO	To Be Assigned	4,920-lb	-	6,000-lb	ST225/75R15	15"	65 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER
810PTO	SALSCO	To Be Assigned	3,840-lb	-	6,000-lb	ST225/75R15	15"	65 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER
813 STANDARD TIRE	SALSCO	To Be Assigned	7,500-lb	7,000-lb	-	ST235/80R16	16"	90 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER
813 WIDE TIRE	SALSCO	To Be Assigned	7,500-lb	7,000-lb	-	12X16.5LT	16.5"	90 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER
813C	SALSCO	To Be Assigned	8,160lb	8,000-lb	-	215/75R17.5	17.5"	125 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER
813XT	SALSCO	To Be Assigned	8,260-lb	7,000-lb	-	12X16.5LT	16.5"	90 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER
813XTC	SALSCO	To Be Assigned	PENDING	8,000-lb	-	235/75R17.5	17.5"	125 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER

PRINT DATE 1/17/2014

## CERTIFICATION LABEL

MODEL	MANUFACTURES NAME	DATE OF MFG	GVWR Gross Vehicle Weight Rating	GAWR Gross Axle Weight Rating (front)	GAWR Gross Axle Weight Rating (rear)	Tire Size	Rim Size	Cold Inflation Pressure (single or dual)	Salsco's Compliance Statement	VIN or WMI #	type of vehicle
818	SALSCO	To Be Assigned	9,600-lb	5,500-lb	5,500-lb	12X16.5LT	16.5"	90 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER
818XT	SALSCO	To Be Assigned	14,420-lb	7,000-lb	7,000-lb	12X16.5LT	16.5"	90 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER
STRAWBLOWER TRAILERED	SALSCO	To Be Assigned	1,140-lb	2,200-lb	-	ST205/75DX14	14"	50 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	STRAWBLOWER
20" SHAVING MILL	SALSCO	To Be Assigned	9,600-lb	7,000-lb	-	ST235/80R16	16"	80 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	SHAVER
30" SHAVING MILL	SALSCO	To Be Assigned	10,800-lb	5,000-lb	5,000-lb	ST225/75R15	15"	65 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	SHAVER
40" SHAVING MILL	SALSCO	To Be Assigned	11,500-lb	7,000-lb	7,000-lb	ST235/80R16	16"	65 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	SHAVER
725	SALSCO	To Be Assigned	1,100-lb	2,000-lb	-	ST205/75D14	14"	50 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	VACUUM
6235B	SALSCO	To Be Assigned	1,490-lb.	2,200-lb	-	ST205/75R14	14"	50PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER
6235BXT	SALSCO	To Be Assigned	1.860-lb	2,200-lb	-	ST205/75R14	14"	50PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	CHIPPER
736K	SALSCO	To Be Assigned	1340-lb	2,200-lb	-	ST205/75D14	14"	50 PSI	THIS UNIT CONFORMS TO ALL APPLICABLE US FEDERAL SAFETY STANDARDS IN EFFECT ON THE DATE OF MANUFACTURE SHOWN ABOVE	To Be Assigned	VACUUM